Cuckoo’yu Çalıştırmak

Cuckoo'yu başlatmak için şu komutu kullanın:

```
$ cuckoo
```

Şuna benzer bir çıktı alacaksınız:

```
  eeee e   e eeee e   e  eeeee eeeee
  8  8 8   8 8  8 8   8  8  88 8  88
  8e   8e  8 8e   8eee8e 8   8 8   8
  88   88  8 88   88   8 8   8 8   8
  88e8 88ee8 88e8 88   8 8eee8 8eee8

 Cuckoo Sandbox 2.0.0
 www.cuckoosandbox.org
 Copyright (c) 2010-2017

 Checking for updates...
 Good! You have the latest version available.

2017-03-31 17:08:53,527 [cuckoo.core.scheduler] INFO: Using "virtualbox" as
machine manager
2017-03-31 17:08:53,935 [cuckoo.core.scheduler] INFO: Loaded 1 machine/s
2017-03-31 17:08:53,964 [cuckoo.core.scheduler] INFO: Waiting for analysis
tasks.
```

Cuckoo, güncellemeleri `api.cuckoosandbox.org` adresindeki uzaktan bir API üzerinden kontrol eder. Bu işlemi devre dışı bırakmak için yapılandırma dosyasındaki `version_check` seçeneğini devre dışı bırakabilirsiniz.

Şimdi Cuckoo çalışmaya hazır ve bekliyor.

Cuckoo, yardım komutu ile gösterildiği gibi bazı komut satırı seçeneklerini kabul eder:

```
```

```
$ cuckoo --help
Usage: cuckoo [OPTIONS] COMMAND [ARGS]...

Invokes the Cuckoo daemon or one of its subcommands.

To be able to use different Cuckoo configurations on the same
machine with the same Cuckoo installation, we use the so-called
Cuckoo Working Directory (aka "CWD"). A default CWD is
available, but may be overridden through the following options -
listed in order of precedence.

* Command-line option (--cwd)
* Environment option ("CUCKOO")
* Environment option ("CUCKOO_CWD")
* Current directory (if the ".cwd" file exists)
* Default value ("~/.cuckoo")

Options:
  -d, --debug             Enable verbose logging
  -q, --quiet             Only log warnings and critical messages
  -m, --maxcount INTEGER  Maximum number of analyses to process
  --user TEXT             Drop privileges to this user
  --cwd TEXT              Cuckoo Working Directory
  --help                  Show this message and exit.

Commands:
  api          Operate the Cuckoo REST API.
  clean        Clean the CWD and associated databases.
  community    Fetch supplies from the Cuckoo Community.
  distributed  Distributed Cuckoo helper utilities.
  dnsserve     Custom DNS server.
  import       Imports an older Cuckoo setup into a new CWD.
  init         Initializes Cuckoo and its configuration.
  machine      Dynamically add/remove machines.
  migrate      Perform database migrations.
  process      Process raw task data into reports.
  rooter       Instantiates the Cuckoo Rooter.
  submit       Submit one or more files or URLs to Cuckoo.
  web          Operate the Cuckoo Web Interface.
```

`--debug` ve `--quiet` flagleri, cuckoo komutu veya herhangi bir alt komut için günlüğün ayrıntısını artırır veya azaltır.

Revision #1
Created 3 January 2024 09:56:43 by Ertan Sözer
Updated 3 January 2024 09:59:40 by Ertan Sözer