

Cuckoo'yu Çalıştırmak

Cuckoo'yu başlatmak için şu komutu kullanın:

```
$ cuckoo
```

Şuna benzer bir çıktı alacaksınız:

```
eeee e  e eeee e  e  eeeee eeeee  
8 8 8 8 8 8 8 8 88 8 88  
8e 8e 8 8e 8eee8e 8 8 8 8  
88 88 8 88 88 8 8 8 8 8  
88e8 88ee8 88e8 88 8 8eee8 8eee8
```

Cuckoo Sandbox 2.0.0

www.cuckoosandbox.org

Copyright (c) 2010-2017

Checking for updates...

Good! You have the latest version available.

```
2017-03-31 17:08:53,527 [cuckoo.core.scheduler] INFO: Using "virtualbox" as  
machine manager
```

```
2017-03-31 17:08:53,935 [cuckoo.core.scheduler] INFO: Loaded 1 machine/s
```

```
2017-03-31 17:08:53,964 [cuckoo.core.scheduler] INFO: Waiting for analysis  
tasks.
```

Cuckoo, güncellemeleri api.cuckoosandbox.org adresindeki uzaktan bir API üzerinden kontrol eder. Bu işlemi devre dışı bırakmak için yapılandırma dosyasındaki `version_check` seçeneğini devre dışı bırakabilirsiniz.

Şimdi Cuckoo çalışmaya hazır ve bekliyor.

Cuckoo, yardım komutu ile gösterildiği gibi bazı komut satırı seçeneklerini kabul eder:

```
$ cuckoo --help  
Usage: cuckoo [OPTIONS] COMMAND [ARGS]...
```

Invokes the Cuckoo daemon or one of its subcommands.

To be able to use different Cuckoo configurations on the same machine with the same Cuckoo installation, we use the so-called Cuckoo Working Directory (aka "CWD"). A default CWD is available, but may be overridden through the following options - listed in order of precedence.

- * Command-line option (--cwd)
- * Environment option ("CUCKOO")
- * Environment option ("CUCKOO_CWD")
- * Current directory (if the ". cwd" file exists)
- * Default value ("~/.cuckoo")

Options:

- | | |
|------------------------|-----------------------------------------|
| -d, --debug | Enable verbose logging |
| -q, --quiet | Only log warnings and critical messages |
| -m, --maxcount INTEGER | Maximum number of analyses to process |
| --user TEXT | Drop privileges to this user |
| --cwd TEXT | Cuckoo Working Directory |
| --help | Show this message and exit. |

Commands:

- | | |
|-------------|-----------------------------------------------|
| api | Operate the Cuckoo REST API. |
| clean | Clean the CWD and associated databases. |
| community | Fetch supplies from the Cuckoo Community. |
| distributed | Distributed Cuckoo helper utilities. |
| dnsserve | Custom DNS server. |
| import | Imports an older Cuckoo setup into a new CWD. |
| init | Initializes Cuckoo and its configuration. |
| machine | Dynamically add/remove machines. |
| migrate | Perform database migrations. |
| process | Process raw task data into reports. |
| rooter | Instantiates the Cuckoo Rooter. |
| submit | Submit one or more files or URLs to Cuckoo. |
| web | Operate the Cuckoo Web Interface. |

--debug ve --quiet flagleri, cuckoo komutu veya herhangi bir alt komut için günlüğün ayrıntısını artırır veya azaltır.

Revision #1

Created 3 January 2024 09:56:43 by Ertan Sözer
Updated 3 January 2024 09:59:40 by Ertan Sözer